

IP20

Art. 807 - *Square spotlight in gypsum*

Mount:	hide-away recess with built-in aluminum brackets suitable for board's thickness from 9 to 15 mm Built-in aluminum flange for a better thermal dissipation with halogen light bulbs
Lampsocket:	GU10 220v + GU5.3 12v*
Energy efficency**:	compatible with lightbulbs from A++ to E classes
Weight:	kg 0,460

Packing 24 pieces
Dimensions: vol.m³ 0,0427 cm 36x32,5x36,5
Weight: gross kg 15 / nett kg 14

* (without converter)
**(lightbulb not included)

Art. 807 - *Faretto quadrato in gesso*

Montaggio:	incasso a scomparsa con staffe incorporate in alluminio per cartongesso da mm 9 a mm 15 Flangia in alluminio per una migliore dissipazione termica con l' impiego di lampadine alogene
Portalampada:	GU10 220v + GU5.3 12v*
Cl.energetica**:	compatibile con lampadine di classe da A++ a E
Peso:	kg 0,460

Imballo 24 pezzi
Dimensioni: vol.m³ 0,0427 cm 36x32,5x36,5
Peso: lordo kg 15 / netto kg 14

* (privo di alimentatore)
**(il dispositivo è privo di lampadina)





